


Lean DL, version 19K R0 14 81 11 5

There are more versions of **Lean DL** available at lival.com
High performance recessed downlight. Tilts 90° and turns 355°,
great for shelf and wall lighting.



| | |
|---------------------------|---|
| Lightsource | LED |
| Article Number | 19K R0 14 81 11 5 |
| Family Name | Lean DL |
| Luminaire Type | Downlight |
| Adapter Type | Cable, 1 m |
| Mounting Type | Recessed in ceiling |
| Light Source Product Name | Citizen CLU038-1206/830 |
| Control Gear | on/off, BLL |
| Light Distribution | Spot |
| Wattage | 42 W |
| Luminous Flux | 4085 lm |
| Efficacy (lm/W) | 97 lm/W |
| COB Flux | 4950 lm |
| Color Temperature | 3000 K |
| Color Rendering Index | Ra 80 |
| Color Of Housing | Silver |
| IP Rating | 20 |
| Lifetime | 50 000h (L80 B10) |
| Light Source Options | CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K |
| Color Consistency | MacAdams 2 SDCM |
| Material | Powder painted die-cast aluminium |
| UGR | 17.8 |



For more information and DLX & LDT downloads visit us at lival.com. We are more than happy to reply to your
email at lival@lival.com or your call at +358-9-235 511