

# Trigger Lean, version 140 R0 14 44 11 5

There are more versions of **Trigger Lean** available at [lival.com](http://lival.com)  
 High performance and cost efficiency. Perfect for recessed tracks  
 due to flush installed housing.



Lightsource	LED
Article Number	140 R0 14 44 11 5
Family Name	Trigger Lean
Luminaire Type	Tracklight
Adapter Type	GA-69
Mounting Type	Track mounted
Light Source Product Name	Citizen CLU038-1206/830
Control Gear	on/off, DALI, BLL
Light Distribution	Spot
Wattage	42 W
Luminous Flux	4085 lm
Efficacy (lm/W)	97 lm/W
COB Flux	4950 lm
Color Temperature	3000 K
Color Rendering Index	Ra 80
Color Of Housing	Silver
IP Rating	20
Lifetime	50 000h (L80 B10)
Light Source Options	CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K
Color Consistency	MacAdams 2 SDCM
Material	Powder painted die-cast aluminium
UGR	17.8

