


Lean Cylinder LED, version 19Q R0 14 44 12 5

There are more versions of **Lean Cylinder LED** available at lival.com
Clean, architectural design and high performance. Flush installation
on lighting track, perfect for recessed tracks.



Lightsource	LED
Article Number	19Q R0 14 44 12 5
Family Name	Lean Cylinder LED
Luminaire Type	Tracklight
Adapter Type	GA-69
Mounting Type	Track mounted
Light Source Product Name	Citizen CLU038-1206/830
Control Gear	on/off, BLL
Light Distribution	Flood
Wattage	44 W
Luminous Flux	4129 lm
Efficacy (lm/W)	94 lm/W
COB Flux	4950 lm
Color Temperature	3000 K
Color Rendering Index	Ra 80
Color Of Housing	Silver
IP Rating	20
Lifetime	50 000h (L80 B10)
Light Source Options	CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K
Color Consistency	MacAdams 2 SDCM
Material	Powder painted die-cast aluminium
UGR	23,5



For more information and DLX & LDT downloads visit us at lival.com. We are more than happy to reply to your
email at lival@lival.com or your call at +358-9-235 511