Lean Mini, version 19L 00 14 44 11 5

There are more versions of **Lean Mini** available at <u>lival.com</u> Compact Lean variation. Flush installation on lighting track, perfect for recessed tracks.

	M	/	
ь	v	/ <u>^</u>	

Lightsource	LED		
Article Number	19L OO 14 44 11 5		
Family Name	Lean Mini		
Luminaire Type	Tracklight		
Adapter Type	GA-69		
Mounting Type	Track mounted		
Light Source Product Name	Citizen CLU038-1206/830		
Control Gear	on/off, BLL		
Light Distribution	Spot		
Wattage	36 W		
Luminous Flux	3831 lm		
Efficacy (Im/W)	106 lm/W		
COB Flux	4350 lm		
Color Temperature	3000 K		
Color Rendering Index	Ra 80		
Color Of Housing	Silver		
IP Rating	20		
Lifetime	50 000h (L80 B10)		
Light Source Options	CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K		
Color Consistency	MacAdams 2 SDCM		
Material	Powder painted die-cast aluminium		
UGR	23.3		





